


JUMBLE

ARMONICALLY BLENDING MATERIALS DIVERSITIES.





JUMBLE AVORIO 45X90 - 18"X36"



JUMBLE AVORIO 22,5X90 - 9"X36"



JUMBLE CEMENTO 22,5X90 - 9\"X36\"



JUMBLE CEMENTO 45X90 - 18\"X36\"



JUMBLE CORTEN 22,5X90 - 9"X36"



JUMBLE CORTEN 45X90 - 18"X36"



JUMBLE CAFFÈ 45X90 - 18"X36"



JUMBLE CAFFÈ 22,5X90 - 9"X36"

TECHNICAL DETAILS

JUMBLE

TECHNOLOGY PORCELLANATO DIGITAL HD AD IMPASTO COLORATO

HD DIGITAL COLORED BODY PORCELAIN

FINISH OPACO RETTIFICATO

NATURAL RECTIFIED

THICKNESS 9,5 MM



JUMBLE COLORS


AVORIO

CEMENTO


CAFFÈ

CORTEN


JUMBLE SIZES




45X90 18"X36"



22,5X90 9"X36"



MOSAIC 22,5x22,5 9"x9"



SKIRTING 7,5x90 3"x36"

JUMBLE CODES

SIZE	COLORS CODE JUMBLE			
	Avorio	Cemento	Caffè	Corten
45x90 18"x36"	4100019	4100018	4100017	4100020
22,5x90 9"x36"	4100013	4100012	4100011	4100014
Mosaic	4100023	4100022	4100021	4100024
Skirting	4100027	4100026	4100025	4100028

JUMBLE PACKING

JUMBLE	pcs	m ²	kg/box	box/pal	m ² /pal	kg/pal
45x90 18"x36"	3	1,215	24,80	36	43,74	892,80
22,5x90 9"x36"	6	1,215	24,80	36	43,74	892,80
Mosaic	10	-	10,00	-	-	-
Skirting	10	-	20,00	-	-	-



NORMA STANDARD	CARATTERISTICHE FEATURES	VALORE PRESCRITTO VALUE REQUIRED	JUMBLE
ISO 10545/2	DIMENSIONI - SIZE lunghezza e larghezza length and width spessore thickness rettilinearità degli spigoli straightness of edges ortogonalità wedging planarità flatness	± 0,6 % / ± 2 mm ± 5 % ± 0,5 % ± 0,6 % ± 0,5 %	± 0,6 % / ± 2 mm ± 5 % ± 0,5 % ± 0,6 % ± 0,5 %
ISO 10545/3	assorbimento d'acqua water absorption	<0,5 %	0,3 %
ASTM C373	water absorption	<0,5 %	meets the standards
ISO 10545/9	resistenza agli sbalzi termici thermal shock	nessuna alterazione visibile no visible alteration	resiste resistant
ASTM C484	thermal shock	unaffected	unaffected
ISO 10545/12	resistenza al gelo frost/freeze resistance	nessuna alterazione visibile no visible alteration	resiste resistant
ASTM C1026	frost/freeze resistance	unaffected	unaffected
ISO 10545/13	resistenza agli attacchi chimici chemical resistance	nessuna alterazione visibile no visible alteration	resiste resistant
ASTM C650	chemical resistance		unaffected
ISO 10545/4	resistenza alla flessione breaking strength	≥ 35 N/ mm ²	45 N/ mm ²
ISO 10545/7	resistenza all'abrasione visible abrasion resistance		PEI V
ASTM C1027	visible abrasion resistance	CLASS I-V	CLASS V
ISO 10545/14	resistenza alle macchie stain resistance	≥ CLASSE 3	5
ASTM C1378	stain resistance	≥ CLASSE 3	5
DIN 51130	scivolosità anti-slip		R10
DCOF	dynamic coefficient of friction	> 0,42	0,69
ANSI A137.1	aesthetic classes	V0-V4	V3

Diversi materiali tra cui pietre di recupero, cementi, resine, marmi e legni fossili sono amalgamati come in una sinfonia in cui i diversi suoni si mescolano e si uniscono, si fondono e si confondono tra loro, così i diversi materiali e le svariate grafiche si mischiano insieme per dare origine a un'unica entità complessa e multiforme.

Abbiamo scelto materiali freddi, primordiali, in quattro colorazioni essenziali: avorio, cemento, caffè, corten.

Different materials including reclaimed stone, cements, resins, marble and fossil woods are mixed as it was a symphony, where the different many sounds mingle and blend, melt and mix each other, so the different materials and the various graphics do to create a new complex and versatile look. We chose cold materials, primordial, essential in four colours: Ivory, cement, coffee, corten.



41zero42.it